

Acryl-Coat

Acrylic Paint Type Coating for Concrete, Stucco, and Walls

Product Description and Uses

Acryl-Coat is a versatile coating material formulated from pure acrylic polymers designed for interior and exterior use. **Acryl-Coat** is a tough and reliable paint that will provide durable and weather resistant surface.

Advantages

Acryl-Coat maintains superior water resistance and resists wind and driven rain. This product is the “work horse” of paints. It is a high quality paint that will protect and beautify any home or business. **Acryl-Coat** can be used on a large variety of surfaces:

- Stucco
- New work
- Repaint
- Masonry
- Concrete
- Brick
- Wood (Primed)
- Hardboard (Primed)
- Aluminum
- Steel (Primed)

Packaging and Mixing

Acryl-Coat is packaged in a 1 gallon, 5 gallon, or 55 gallon container. It is recommended that this product is **not** reduced with water before use. Shake or stir liquid thoroughly before use. **Acryl-Coat** is packaged ready to use and may be applied with a brush, roller, or sprayed on.

Coverage

Approx. 100 sq ft per gallon when applied at the recommended 4 to 6 mil. dry film thickness.

Technical Properties

Appearance	White, flat
Drytime @ 70 F and 50% RH:	
-to touch	30 minutes
-to recoat	4 hours
Solids	- 63%
Federal Standard Accelerated Weathering	- No growth of fungus - 2000 hrs. with no affect on color or film integrity.
Flash Point	- none
Salt Spray Resistance	- 300 hrs. with no deterioration or other affects.
Moisture Resistance	- 14 day exposure with no deleterious affects.

Limitations

Apply over clean surfaces, remove any debris/chemical that will interfere with adhesion. All surfaces must be properly cured. Do not apply in below 40 degrees F. Apply **Acryl-Coat** when there is no threat of rain, dew, or frost. Refer to MSDS sheets for additional health and safety precautions.

***Sur-Cure R1831** sealer is recommended as primer for all concrete, stucco, and masonry surfaces.