

# Sun Flex Caulking

## *Elastomeric Joint Sealant*

### Product Description and Uses

**Sun Flex Caulking** is a heavy bodied emulsion type, gun grade elastomeric, high build waterproof sealant. **Sun Flex Caulking** has outstanding elongation properties which allows it to contract and expand with substrates, thereby maintaining a constant seal. An ideal patching material that stays flexible to permanently stop leaks and seal mildew. Adheres to a wide range of surfaces:

- Plywood and Concrete
- Shingles, wood, or asphalt
- Built up Roofing
- Mineral Roll Roofing
- Sheet Metal
- Stucco and tile
- Drywall
- Plastic

### Advantages

- ✓ Complete weathproofing. Withstands wind, driven rain, salt spray, and ponding water.
- ✓ Tenacious adhesion – bonds to almost anything.
- ✓ Great for patching hairline cracks and filling expansion joints.
- ✓ Economical – less material is needed, saving money in material
- ✓ Easy to apply with caulking gun, brush, or broad knife.
- ✓ Water based – environmentally friendly.
- ✓ Resistant to UV degradation.
- ✓ Seals windows and door frames.
- ✓ Low maintenance, easy to repair.

### Packaging and Mixing

**Sun Flex Caulking** is packaged ready to go out of the pail or tube, do not dilute. Also, **Sun Flex Caulking** exhibits a white color, which makes it easier to see when painting and repairing. This single component material is available in 10 oz. tubes, 1 gal. pails and 5 gal. pails.

### Coverage

Rates per 40 sq ft at 1/16” thickness:  
Approx. 1 gallon.  
\*Rates will vary depending upon type, porosity, and condition of surface.

### Surface Preparation and Installation

All surfaces to be treated need to be completely dry and free of all dirt, oil, or any other contaminants that would impair the adhesion of **Sun Flex Caulking**. Allow for shrinkage. Apply 2 coats to cracks over 1/4”, allowing 3-4 hrs. between coats. Feather the edges of all repairs to hide area.

### Limitations

Do not apply in below 40 degrees F or in high humidity conditions. Apply **Sun Flex Caulking** when there is no threat of rain, dew or frost. Refer to MSDS sheets for additional health and safety precautions.